



Developed to fulfill  
**your highest**  
expectations.



→ [www.trennex.de](http://www.trennex.de)



*"Trennex has been active in the field of Minimum Quantity Spraying for die casting for nearly 10 years. Through continuous and customer-oriented R&D, we have built up a wide portfolio of Minimum Quantity Spraying lubricants that can be used to fulfill different requirements. With these products, we helped many customers implement Minimum Quantity Spraying into their production facilities' series production. The implementation of Minimum Quantity Spraying into a plant's series production is always a challenge. That is why it is important to be supported in this process by a reliable and experienced partner. Our highly effective and flexible Applications Technology and Development Department will be at your side, every step of the way. Speak with us – Challenge us"*

Helmut Geiger, Managing Director

TRENNEX®

**MS W 051**

**MS W 058**

**MS W 060**

**MS W 068**

Wax-free high performance  
lubricants,

**MS W 038**

Wax-free and polysiloxane-free high  
performance lubricant,

developed specifically for  
Minimum Quantity Spraying (MQS).

- » Developed specifically for technically sophisticated parts
- » Reliably wets the tool, even at high tool temperatures
- » The classic Leidenfrost-Effect is reduced by using our **MQS** products

**In order to avoid over-lubrication, the correct spray equipment must be used!**

TRENNEX®

**VM 3386**

Water-free high performance  
lubricant,

developed specifically for  
Minimum Quantity Spraying (MQS).

- » Developed specifically for technically sophisticated parts
- » Reliably wets the tool up to tool temperatures of app. 350 up to max. 400°C

**In order to avoid over-lubrication, the correct spray equipment must be used!**



**Geiger + Co.**  
**Schmierstoff-Chemie GmbH**  
D-74008 Heilbronn | [info@trennex.de](mailto:info@trennex.de)