



"Trennex has been active in the field of Minimum Quantity Spraying for die casting for more than 12 years.

Through continuous and customeroriented R&D, we have built up a wide portfolio of Minimum Quantity Spraying lubricants that can be used to fulfill different requirements.

With these products, we helped many customers implement Minimum Quantity Spraying into their production facilities' series production.

The implementation of Minimum Quantity Spraying into a plant's series production is always a challenge.

That is why it is important to be supported in this process by a reliable and experienced partner.

Our highly effective and flexible Applications Technology and Development Department will be at your side, every step of the way.

Speak with us - Challenge us"

TRENNEX®

MS W 060 MS W 063 MS W 068 MS W 070

Wax-free high performance lubricants,

## MS W 038

Wax-free and polysiloxane-free high performance lubricant,

developed specifically for Minimum Quantity Spraying (MQS).

- » Developed specifically for technically sophisticated parts
- » Reliably wets the tool, even at high tool temperatures, thanks to the latest additives
- The classic Leidenfrost-Effect is reduced by using our MQS products

In order to avoid over-lubrication, the correct spray equipment must be used!

TRENNEX® VM 3386

Water-free high performance lubricant,

developed specifically for Minimum Quantity Spraying (MQS).

- » Developed specifically for technically sophisticated parts
- » Reliably wets the tool up to tool temperatures of app. 350 up to max. 400°C

In order to avoid over-lubrication, the correct spray equipment must be used!

Helmut Geiger, Managing Director



